

The Indigo MG bare system is independently tested and certified to PSA MOB PF2 PS/SPU March 1992

Typical Applications

- Offices
- Casinos
- Education

Indigo MGBare

- ✓ Fully steel encased
- ✓ High-density chipboard core
- ✓ Excellent Dimensional Stability
- ✓ Superior Adhesive Technology
 - will not delaminate
- ✓ Highest Density Chipboard Available



TECHNICAL SPECIFICATION	LOAD CHARACTERISTICS	DIMENSIONS	COMPONENT DETAIL
PSA MOB PF2 PS/SPU	WORKING POINT LOAD 3.0kN ULTIMATE POINT LOAD 9.0kN	MODULE SIZE 600x600mm	Panel: high-density chipboard core Fully encased steel wrap.
MEDIUM GRADE	WORKING UDL 12.0kN/M ² ULTIMATE UDL 36.0kN/M ²	THICKNESS 29mm	Pedestal: Heavy gauge steel construction. ABS Conductive Cap
	SAFETY FACTOR 3	WEIGHT 10Kg	

ACCESS FLOORS DISTRIBUTION LIMITED

PO Box 650
HUNTINGDON, Cambs
PE29 9HF
T/01480 367096
F/01480 330 004

E/sales@accessfloorsdistribution.co.uk
W/www.accessfloorsdistribution.co.uk